

Package: kgen (via r-universe)

August 27, 2024

Type Package

Title A Tool for Calculating Stoichiometric Equilibrium Constants (Ks) for Seawater

Version 0.3.1

License MIT + file LICENSE

Description A unified software package simultaneously implemented in 'Python', 'R', and 'Matlab' providing a uniform and internally-consistent way of calculating stoichiometric equilibrium constants in modern and palaeo seawater as a function of temperature, salinity, pressure and the concentration of magnesium, calcium, sulphate, and fluorine.

Encoding UTF-8

Depends R (>= 4.0)

Imports rjson (>= 0.2.21), reticulate (>= 1.26), rappdirs (>= 0.3.3), checkmate (>= 2.1.0), pbapply (>= 1.7.0), data.table (>= 1.14.6)

Suggests testthat (>= 3.0.0)

RxygenNote 7.2.3

Config/testthat/edition 3

NeedsCompilation no

Author Dennis Mayk [aut, cre]
(<<https://orcid.org/0000-0002-5017-1495>>)

Maintainer Dennis Mayk <dm807@cantab.ac.uk>

Date/Publication 2023-12-19 14:10:02 UTC

Repository <https://dm807cam.r-universe.dev>

RemoteUrl <https://github.com/cran/kgen>

RemoteRef HEAD

RemoteSha 96ceaab80576bad6f8ab4871a10ed9729b3cac0b

Contents

calc_fluorine	2
calc_ionic_strength	3
calc_K	3
calc_K0	5
calc_K1	6
calc_K2	6
calc_KB	7
calc_KF	7
calc_KP1	8
calc_KP2	8
calc_KP3	9
calc_KS	9
calc_KSi	10
calc_Ksp	10
calc_KW	11
calc_pc	11
calc_pressure_correction	12
calc_seawater_correction	12
calc_sulphate	13
install_pmyami	14
is_linux	14
is_osx	14
is_windows	14
kgen_poly	15
K_fns	15
mc_exists	16
miniconda_conda	16
miniconda_path	16
miniconda_path_default	17
pmyami_exists	17

Index	18
--------------	-----------

calc_fluorine *Calculate fluorine*

Description

Calculate fluorine

Usage

`calc_fluorine(sal)`

Arguments

<code>sal</code>	Salinity
------------------	----------

Value

fluorine

References

From Dickson et al., 2007, Table 2, Note: Sal / 1.80655 = Chlorinity

calc_ionic_strength *Ionic strength after Dickson (1990a); see Dickson et al. (2007)*

Description

Ionic strength after Dickson (1990a); see Dickson et al. (2007)

Usage

calc_ionic_strength(sal)

Arguments

sal Salinity

Value

Ionic strength

calc_K *Calculate a single equilibrium constant*

DescriptionCalculate a **single** specified stoichiometric equilibrium constant at given temperature, salinity, pressure and the concentration of magnesium, calcium, sulphate, and fluorine.**Usage**

```
calc_K(  
  k,  
  temp_c = 25,  
  sal = 35,  
  p_bar = NULL,  
  magnesium = 0.0528171,  
  calcium = 0.0102821,  
  sulphate = NULL,  
  fluorine = NULL,
```

```

    method = "r_polynomial"
)

calc_Ks(
  ks = NULL,
  temp_c = 25,
  sal = 35,
  p_bar = NULL,
  magnesium = 0.0528171,
  calcium = 0.0102821,
  sulphate = NULL,
  fluorine = NULL,
  method = "r_polynomial"
)

calc_all_Ks(
  temp_c = 25,
  sal = 35,
  p_bar = NULL,
  magnesium = 0.0528171,
  calcium = 0.0102821,
  sulphate = NULL,
  fluorine = NULL,
  method = "r_polynomial"
)

```

Arguments

k	K to be calculated
temp_c	Temperature (Celcius)
sal	Salinity
p_bar	Pressure (Bar) (optional)
magnesium	magnesium concentration in mol/kgsw. If None, modern is assumed (0.0528171). Should be the average magnesium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.
calcium	calcium concentration in mol/kgsw. If None, modern is assumed (0.0102821). Should be the average calcium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.
sulphate	Sulphate concentration in mol/kgsw. Calculated from salinity if not given.
fluorine	Fluorine concentration in mol/kgsw. Calculated from salinity if not given.
method	string describing method which should be either 'myami', 'myami_polynomial', or 'r_polynomial' (Default: 'r_polynomial').
ks	character vectors of Ks to be calculated e.g., c("K0", "K1") (Default: NULL, calculate all Ks)

Value

- A **single** K at given conditions
- Data.table of **multiple** Ks at given conditions
- Data.table of **all** Ks at given conditions

Functions

- `calc_Ks()`: Wrapper to calculate **multiple** stoichiometric equilibrium constants at given temperature, salinity, pressure and the concentration of magnesium, calcium, sulphate, and fluorine.
- `calc_all_Ks()`: Wrapper to calculate **all** stoichiometric equilibrium constants at given temperature, salinity, pressure and the concentration of magnesium, calcium, sulphate, and fluorine.

Author(s)

Dennis Mayk

calc_K0

Calculate K0

Description

Calculate K0

Usage

```
calc_K0(coefficients, temp_c, sal)
```

Arguments

<code>coefficients</code>	Coefficients for K calculation
<code>temp_c</code>	Temperature (Celcius)
<code>sal</code>	Salinity

Value

K0

calc_K1*Calculate K1*

Description

Calculate K1

Usage

```
calc_K1(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

K1

calc_K2*Calculate K2*

Description

Calculate K2

Usage

```
calc_K2(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

K2

calc_KB

Calculate KB

Description

Calculate KB

Usage

```
calc_KB(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KB

calc_KF

Calculate KF

Description

Calculate KF

Usage

```
calc_KF(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KF

calc_KP1*Calculate KP1*

Description

Calculate KP1

Usage

```
calc_KP1(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KP1

calc_KP2*Calculate KP2*

Description

Calculate KP2

Usage

```
calc_KP2(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KP2

`calc_KP3`*Calculate KP3*

Description

Calculate KP3

Usage

```
calc_KP3(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KP3

`calc_KS`*Calculate KS*

Description

Calculate KS

Usage

```
calc_KS(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KS

`calc_KSi`*Calculate KSi*

Description

Calculate KSi

Usage

```
calc_KSi(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KSi

`calc_Ksp`*Calculate Ksp*

Description

Calculate Ksp

Usage

```
calc_Ksp(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

Ksp

calc_KW	<i>Calculate KW</i>
---------	---------------------

Description

Calculate KW

Usage

```
calc_KW(coefficients, temp_c, sal)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
sal	Salinity

Value

KW

calc_pc	<i>Calculate pressure correction factor for Ks</i>
---------	--

Description

Calculate pressure correction factor for Ks

Usage

```
calc_pc(coefficients, temp_c, p_bar)
```

Arguments

coefficients	Coefficients for K calculation
temp_c	Temperature (Celcius)
p_bar	Pressure (Bar)

Value

Pressure correction factor

References

From Millero et al. (2007, doi:10.1021/cr0503557), Eqns 38-40

calc_pressure_correction*Calculate pressure correction factor***Description**

Calculate pressure correction factor for a specified equilibrium constant.

Usage

```
calc_pressure_correction(k, temp_c, p_bar)
```

Arguments

k	K to be calculated
temp_c	Temperature (Celcius)
p_bar	Pressure (Bar)

Value

pressure correction factor

Author(s)

Dennis Mayk

calc_seawater_correction*Kgen seawater composition correction function***Description**

Kgen seawater composition correction function

Usage

```
calc_seawater_correction(
    k,
    sal,
    temp_c,
    magnesium = 0.0528171,
    calcium = 0.0102821,
    method = "r_polynomial"
)
```

Arguments

k	K to be calculated
sal	Salinity
temp_c	Temperature (Celcius)
magnesium	magnesium concentration in mol/kgsw. If None, modern is assumed (0.0528171). Should be the average magnesium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.
calcium	calcium concentration in mol/kgsw. If None, modern is assumed (0.0102821). Should be the average calcium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.
method	string describing method which should be either 'myami', 'myami_polynomial', or 'r_polynomial' (Default: 'r_polynomial').

Value

list of seawater correction factors

Author(s)

Dennis Mayk

calc_sulphate

Calculate sulphate

Description

Calculate sulphate

Usage

calc_sulphate(sal)

Arguments

sal	Salinity
-----	----------

Value

sulphate

References

From Dickson et al., 2007, Table 2, Note: Sal / 1.80655 = Chlorinity

install_pymyami *Install MyAMI from pypi*

Description

Function to install pymyami in a default location.

Usage

```
install_pymyami()
```

is_linux *Check if OS is Linux*

Description

Check if OS is Linux

Usage

```
is_linux()
```

is_osx *Check if OS is OSX*

Description

Check if OS is OSX

Usage

```
is_osx()
```

is_windows *Check if OS is Windows*

Description

Check if OS is Windows

Usage

```
is_windows()
```

kgen_poly	<i>Kgen R polynomial function</i>
-----------	-----------------------------------

Description

Kgen R polynomial function

Usage

```
kgen_poly(sal, temp_c, magnesium = 0.0528171, calcium = 0.0102821)
```

Arguments

sal	Salinity
temp_c	Temperature (Celcius)
magnesium	magnesium concentration in mol/kgsw. If None, modern is assumed (0.0528171). Should be the average magnesium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.
calcium	calcium concentration in mol/kgsw. If None, modern is assumed (0.0102821). Should be the average calcium concentration in seawater - a salinity correction is then applied to calculate the magnesium concentration in the sample.

Author(s)

Dennis Mayk

K_fns	<i>List of all functions</i>
-------	------------------------------

Description

List of all functions

Usage

```
K_fns
```

Format

An object of class `list` of length 13.

mc_exists	<i>Check if miniconda exists</i>
-----------	----------------------------------

Description

Check if miniconda exists

Usage

```
mc_exists(path = miniconda_path())
```

Arguments

path	Path to miniconda
------	-------------------

miniconda_conda	<i>Check if miniconda is installed</i>
-----------------	--

Description

Check if miniconda is installed

Usage

```
miniconda_conda(path = miniconda_path())
```

Arguments

path	Path to miniconda
------	-------------------

miniconda_path	<i>Get miniconda path</i>
----------------	---------------------------

Description

Get miniconda path

Usage

```
miniconda_path()
```

`miniconda_path_default`

Get miniconda default path

Description

Get miniconda default path

Usage

`miniconda_path_default()`

`pymyami_exists`

Check if pymyami is installed

Description

Check if pymyami is installed

Usage

`pymyami_exists()`

Index

* datasets

K_fns, 15

calc_all_Ks (calc_K), 3

calc_fluorine, 2

calc_ionic_strength, 3

calc_K, 3

calc_K0, 5

calc_K1, 6

calc_K2, 6

calc_KB, 7

calc_KF, 7

calc_KP1, 8

calc_KP2, 8

calc_KP3, 9

calc_KS, 9

calc_Ks (calc_K), 3

calc_KSi, 10

calc_Ksp, 10

calc_KW, 11

calc_pc, 11

calc_pressure_correction, 12

calc_seawater_correction, 12

calc_sulphate, 13

install_pymyami, 14

is_linux, 14

is_osx, 14

is_windows, 14

K_fns, 15

kgen_poly, 15

mc_exists, 16

miniconda_conda, 16

miniconda_path, 16

miniconda_path_default, 17

pymyami_exists, 17